



# Technical Data Sheet

## L515

### SEMI GLOSS DOT MATRIX WHITE PAPER

**GENERAL DESCRIPTION:** L515 is a semi-gloss white paper. It is coated with a general removable acrylic adhesive and backed with a 40# Kraft release liner.

**USES:** Ideal for marking packages, bags and corrugated cardboard. The ultra smooth semi gloss finish offer excellent clarity of pre-printed flexo graphic images/information. Not recommended for labeling highly curved surfaces

**FEATURES:** Indoor only. Great material to be used where the label needs to be cleanly removed after it is applied for some time. This material is recommended for completely pre-printed packaging labels.

**RECOGNITION(S):** RoHS Directive 2002/95/EC Compliant

**RECOMMENDED RIBBON:** NSR

<b>PHYSICAL PROPERTIES:</b>	<b>TEST METHODS</b>	<b>CONVENTIONAL UNITS</b>	<b>S.I. UNITS</b>
<b>THICKNESS:</b>	Film	3.0 mils	76 microns
	Adhesive	.5 mils	12.7 microns
	Liner(40#)	2.5 mils	63.5 microns
	Total	6.0 mils	152.2 microns

**ADHESIVE PERFORMANCE:** No Data Available

---

**WARRANTY**  
 "Our products are sold with the understanding that the buyer will test them in actual use and determine for himself their adaptability to his intended uses. We warrant to the buyer that our products are free from defects in material and workmanship. This warranty is in lieu of any other warranty, expressed or implied"

**SERVICE TEMPERATURE:**

-0°F - 175°F

-17°C - 79°C

**MINIMUM APPLICATION TEMPERATURE:**

40°F

4°C

**EXTERIOR  
DURABILITY:**

Indoor Only

Label Stock: No Effect

**CHEMICAL RESISTANCE:**

No chemical testing has been completed. If there is any testing required, please contact your Identco representative to request such testing

**STORAGE STABILITY**

Product should be stored at 70°F (21°C) and 40-50% relative humidity to ensure optimal performance.

**SHELF LIFE:**

1 year @ proper storage conditions