

CP3010




Labels for Life.

Face Stock: 3.5 mil flexible gloss white vinyl provides exceptional surface smoothness and conformability. The material offers excellent resistance to moderate temperatures and harsh abrasions.

Adhesive: 2.0 mil permanent pressure-sensitive acrylic adhesive provides excellent adhesion to low and high surface energy plastics, painted metal, powder-coated paint, polycarbonates and fiberglass. The adhesive offers excellent resistance to high temperatures and harsh abrasions.

Release Liner: 50# kraft release liner.



Calendared White Vinyl Film

CP3010 is specifically designed to be UV Screen & Flexo printable and withstand the harsh environments of the Outdoor Power industry. Key features include: outdoor power compliant, heavy duty adhesive, excellent abrasion and heat resistance, conformable and it will not shrink. When used in combination with the recommended IDENTCO inks it will meet the most demanding durable labeling requirements needed to exceed Outdoor Power Equipment compliance regulations.

Typical Applications

Outdoor Power Equipment
Compliance Labeling
Nameplates
Fiberglass, Polycarbonates,
Powder-Coated Paint, & Plastics.

Typical Industry Sectors

Outdoor Power Equipment
Power Tools
Appliances.



www.identco.com

CP3010

Calendared White Vinyl Film



Labels for Life.

	Agency Recognitions UL-MH16225
	Adhesion Stainless Steel 94 oz/in 1034 N/m Acrylic 130 oz/in 1430 N/m
	Material Caliper Face Stock .0035" 88.9µ Liner (kraft/FL) .0031" 175.3µ Adhesive .0020" 50.8µ Total Material .0086" 218.4µ
	Exterior Durability Material Only: Indoor & 5 year outdoor durability Testing: 2000 hours in Xenon Arc
	Temperature Range Service Temperature: -40°F to 176°F (-40°C to 80°C) Minimum Application Temperature: 50°F (10°C)
	Shelf Life Recommended Storage: 45-90°F (7-32°C) 20-75% R.H. Shelf Life: 2 years @ recommended storage
	Recommended Inks UV Flexo UV Screen
	Process Durability It is recommended that customers test this material in actual application to determine if the material meets all requirements.

Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by IDENTCO customers for designs and specifications, or be relied on as meeting specific performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact IDENTCO for further information. Revised 11/1/2016

UNITED STATES HEADQUARTERS

28164 W. Concrete Drive
Ingleside, IL 60041
Phone: +1 (815) 385 - 0011
Fax +1 (815) 385 - 0359

MEXICO MONTERREY

Carr. a Laredo Km. 16.5 Interior
14B, Col. Moisés Sáenz, 66613
Apodaca, Nuevo Leon
Phone: +52 (81) 8008 - 0438

GERMANY FRANKFURT

Güterbahnhofstrasse 3-7
63450 Hanau
Phone: +49 (6181) 440 830 - 0
Fax: +49 (6181) 440 830 - 99

PRC HONG KONG

Unit 1708, 17/F, 9 Wing Hong St.
Cheung Sha Wan, Kowloon
Phone: +852 2959 2156
Fax: +852 2959 2019

MALAYSIA PENANG

Suite 163E, Level 16, Room 1602
Hunza Tower Gurney Paragon
Jalan Kelawei, Georgetown
10250 Penang
Phone: +6012 466 - 0866